

ARES LRF 2.0 Series Thermal Imaging

Thermal Tube Scope Ares335L 2.0

Technical Specifications











ThermTec Technology Co., Ltd. Email: info@thermeyetec.com Website: https://www.thermeyetec.com

Ares335L 2.0

Key Features

- 384*288 thermal resolution, NETD≤18mK;
- 5 colors and 7 reticle choices for reticle options;
- Freeze and zoom of zeroing improve shooting accuracy.;
- Built-in laser rangefinder, accurately measure the distance up to 1,000m;
- Self-learning image calibration;
- Ultra-long battery life reaches to 18hrs;
- 5 zeroing profiles meet various needs;
- RAV function allows recording every terrific shot;
- Rotary knob design;
- Support video recording and snapshot, built-in memory chip up to 64GB;

Applications

- Night hunting
- Observation

Specifications

_		1		
	ľ			

Model	ARES335L 2.0			
Microbolometer				
Туре	Uncooled			
Resolution	384x288			
Pixel pitch	12μm			
NETD	≤18mK			
Spectral range	8-14µm			
Frame rate	50HZ			
Detection Range	1800m			
	Optics			
Objective lens	35mm, F1.0			
Field of view	7.5°x5.6°			
m@100m	13.2x9.9			
Magnification	3.2X			
Digital zoom	1.0-4.0X smooth & rapid zoom			
Eye relief	50mm			
Exit pupil	6mm			
Diopter	±5D			
	Aiming Reticle			
Reticle	7			
Reticle color	5,Black. white, red, green, blue			
	Display			
Туре	AMOLED			
Resolution	1024x768			
Display size	0.39 inch			
Color palette	6			

Function				
Max. recoil power on rifled weapon	6000J			
Mounting brackets on weapon	Standard 30mm rings			
RAV	Yes			
Audio Recording	Yes			
Auto zeroing	Yes			
Manual zeroing	Yes			
Zeroing profiles	5			
Freeze Zeroing	Yes			
Picture-in-picture	Yes			
Laser ranging	1.8mrad@1000m			
Ballistic Calculator	Yes			
Image calibration	Manual/Auto			
	Video Recorder			
Phone/video playback	Yes			
Inbuilt memory	64GB			
	Interface			
Type C	Data transfer			
Hotspot	Yes			
Battery				
Battery type	Replaceable, 1*18650 or 18500 battery,1*18650 inbuilt battery			
Battery reverse connection	nection Yes			
Battery life	18h			
	Environment			
Operating temperature	-20- +50°C			
IP rating	IP67			
Weight, g	849			
Size, mm	391.8*85.3*82.2			
	Accessories			
External cable	USB data cable			
Other accessory	2x standard 30mm rings, eyeshade and etc.			

Accessories





Eyeshade (x1)



Lithium battery (x2)



18650 battery cap (x1)



18500 battery cap (x1)



Charger(X1)



USB cable (x1)



30mm tube clip (x2)



Lens cloth (x1)

Dimension

Unit: mm



